



BES2600Z

Brief Datasheet

Ultra-low Power Bluetooth and LE Audio Platform

CONTACT US:

Company: Bestechnic (Shanghai) Co., Ltd. (“BES”)

Address: 2F, Building B, Lane 2889 Jinke Road, Pudong, Shanghai (201203)

Phone: (86)21 6877 1788

For product inquiries and more information, please visit www.bestechnic.com.


DISCLAIMER:

No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, for any purpose, without the express written permission of BES. BES retains the right to make changes to this document at any time, without notice. BES makes no warranty of any kind, expressed or implied, with regard to any information contained in this document, including, but not limited to, the implied warranties of merchant ability or fitness for any particular purpose. Further, BES does not warrant the accuracy or completeness of the information, text, graphics, or other items contained within this document.

1 General Description

The BES2600Z is an ultra-low power Bluetooth audio SoC. The platform incorporates a high performance CPU subsystem comprising a dual-core STAR-MC1 with a BECO NPU, a BES proprietary coprocessor for advance signal processing and NN workloads, a sensor hub subsystem comprising a STAR-MC1 processor, RAM/ROM, serial flash for software features and product customization, as well as a variety of interfaces.

The platform integrates a dual-mode Bluetooth 5.3 subsystem for both Bluetooth classic and LE audio, and an audio codec subsystem supporting voice activity detection. The highly integrated solution is optimized through the use of IBRT technology, a BES patented sniffing technique that incorporates a 0.6 (o)-2 ((us)2 Tc -0.00/go)80 Tc for the (o)-0.9(r)6 (o) performance in TWs systems.



1.2 Features & Specifications*

CPU Subsystem	STAR-MC1
Sensor Hub Subsystem	STAR-MC1
Memory and Storage	Shared 1.2 MB SRAM
	Flash in package
	boot ROM
Bluetooth Subsystem	Dual-mode BT 5.3 with LE audio
Audio & Voice Features	1x DAC
	4x ADCs
Peripheral Interfaces	GPADC/SPI/I2C/UART/I2S/TDM/SPDIF/DMIC/GPIO.....
Package	108-ball BGA

* The content in the table is subject to change without notice.